

Photomultiplier tube PMT190

The photomultiplier PMT190 has a translucent antimony-sodium-potassium photocathode with spectral characteristics in the area 350 is 650 nm, the electrostatic focusing of electrons, 12-dynode multiplied system louvered type, flat face optical input and reflex output, a built-in low-voltage divider; made in glass-to-metal shell filled with polyurethane foam dielectric housing with a flexible wires. Photomultiplier is used in electronic devices of general application, working in conditions of high mechanical and climatic loads, to convert light signals into electrical.

Technical specification

Parameter, unit	Standard		
	No less	Nominal	No more
Constructive dimensions			
Diameter (max), mm		40	
Useful photocathode diameter, mm		25	
Fit length, mm		110 _{2,4}	
Weight, g		140	
Electrical and lighting parameters			
Luminous photocathode sensitivity, blue, A/lm	4×10^{-5}	-	-
Spectral sensitivity of the photocathode at the wavelength 410 nm, A/Wt	$3,5 \times 10^{-2}$	-	-
Luminous anode sensitivity, A/lm	-	10	-
Supply voltage, V	-	-	1700
Dark current, A	-	-	$1,5 \times 10^{-9}$
Energetic resolution, %	-	-	12
Energy equivalent of its noise, keV	-	-	3
Instability, %	-	-	10
Position of maximum spectral characteristics, nm	400	-	440
Resistance to external factors			
Sinusoidal vibration (vibration strength):			
- frequency range, Hz		1÷3000	
- acceleration amplitude, m/s ² (g)		300 (30)	
Mechanical shock of repeated action with peak shock acceleration, m/s ² (g)		1500 (150)	
Operating temperature of ambient, °C		minus 40; +125	
High pressure air, kPa (kgf/cm ²)		294 (3)	
Low working pressure, kPa (mm Hg)		70 (525)	
MTF, h		2000	



EKRAN
OPTICAL SYSTEMS

JSC «Ekran - optical systems»
630047 Russia, Novosibirsk, Dargomyzhskogo 8a

F: +7(383)325-17-58 M: info@ekran-os.ru www.ekran-os.ru