



EKRAN
OPTICAL SYSTEMS



PMT



Photomultiplier tube PMT-110

The photomultiplier PMT-110 has a translucent antimony-potassium-sodium-cesium photocathode with spectral characteristics in the area of 300 is 900 nm, the electrostatic focusing of electrons, 12-dynode multiplied system of louvered type, flat face optical input and reflex output; made without socle design with tough wires. The photomultiplier is used in electronic devices of general application to convert light signals into electrical.

Technical specification

Parameter, unit	Standard		
	No less	Nominal	No more
Constructive dimensions			
Diameter (max), mm	80		
Useful photocathode diameter, mm	63		
Fit length, mm	125 ₋₆		
Weight, g	200		
Electrical and lighting parameters			
Luminous photocathode sensitivity, A/lm	1,2x10 ⁻⁴	-	-
Luminous anode sensitivity, A/lm	-	10	-
Supply voltage, V	-	-	1500
Dark current, A	-	-	3,5x10 ⁻⁹
Energetic resolution, %	-	-	11
Nonlinearity of luminescence characteristics in impulse regime,%	-	-	20
Energy equivalent of its noise, keV	-	-	3
Insulation resistance, MOm	10 ³	-	-
Instability, %	-	-	5
Maximum position of spectral characteristics, nm	420	-	520
Resistance to external factors			
Sinusoidal vibration (vibration strength):			
- frequency range, Hz	1÷2000		
- acceleration amplitude, m/s ² (g)	100 (10)		
Mechanical shock of repeated action with peak shock acceleration, m/s ² (g)	400 (40)		
Operating temperature of ambient, °C	minus 60; +70		
High pressure air, kPa (kgf/cm ²)	294 (3)		
Low working pressure, kPa (mm Hg)	53,3 (400)		
MTF, h	3000		



EKRAN
OPTICAL SYSTEMS

JSC «Ekran - optical systems»
630047 Russia, Novosibirsk, Dargomyzhskogo 8a

F: +7(383)325-17-58 M: info@ekran-os.ru www.ekran-os.ru